

#### ITW AAMTech Australia

Chemwatch: **7503-35** Version No: **8.1.1.1** 

Safety Data Sheet according to WHS and ADG requirements

#### Chemwatch Hazard Alert Code:

Issue Date: **08/05/2015**Print Date: **08/12/2016**S.GHS.AUS.EN

#### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	Septone C-Thru		
Synonyms	window glass cleaner		
Other means of identification	Not Available		

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified	Window and glass cleaner.
uses	

# Details of the supplier of the safety data sheet

Registered company name	ITW AAMTech Australia		
Address	Nina Link, Dandenong South VIC 3175 Australia		
Telephone	00 177 989		
Fax	1800 308 556		
Website	www.aamtech.com.au		
Email	info@aamtech.com.au		

#### **Emergency telephone number**

Association / Organisation	Not Available			
Emergency telephone numbers	1800 039 008			
Other emergency telephone numbers	0800 2436 2255			

#### **SECTION 2 HAZARDS IDENTIFICATION**

# Classification of the substance or mixture

### NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
Classification	Not Applicable

#### Label elements

GHS label elements	Not Applicable
SIGNAL WORD	NOT APPLICABLE

#### Hazard statement(s)

Not Applicable

#### Precautionary statement(s) Prevention

Chemwatch: **7503-35**Page **2** of **10**Version No: **8.1.1.1**September C. T.

Septone C-Thru

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

#### Precautionary statement(s) Response

Not Applicable

#### Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

Not Applicable

#### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### **Substances**

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name			
67-63-0	<10	sopropanol			
Not Available	<10	non hazardous ingredients			
141-43-5	<1	<u>ethanolamine</u>			
34590-94-8	<1	dipropylene glycol monomethyl ether			
7732-18-5	>60	water			

#### **SECTION 4 FIRST AID MEASURES**

#### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  • Wash out immediately with fresh running water.  • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  • Seek medical attention without delay; if pain persists or recurs seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

To treat poisoning by the higher aliphatic alcohols (up to C7):

- ► Gastric lavage with copious amounts of water.
- $\,\blacktriangleright\,$  It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- ullet To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- ▶ Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5)

Issue Date: 08/05/2015

Print Date: 08/12/2016

Chemwatch: **7503-35**Version No: **8.1.1.1** 

Page 3 of 10

Septone C-Thru

Issue Date: **08/05/2015** Print Date: **08/12/2016** 

. . .

#### BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- · Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ► Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for shock.
- Monitor and treat, where necessary, for pulmonary oedema.
- · Anticipate and treat, where necessary, for seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

\_\_\_\_\_

#### ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Fatart an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

.....

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- · Acidosis may respond to hyperventilation and bicarbonate therapy.
- ▶ Haemodialysis might be considered in patients with severe intoxication.
- Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

#### **SECTION 5 FIREFIGHTING MEASURES**

#### **Extinguishing media**

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

▶ foam.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

# Advice for firefighters

#### Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear breathing apparatus plus protective gloves in the event of a fire.
- ▶ Prevent, by any means available, spillage from entering drains or water courses.
- ▶ Use fire fighting procedures suitable for surrounding area.

- ► The material is not readily combustible under normal conditions.
- However, it will break down under fire conditions and the organic component may burn.
- ▶ Not considered to be a significant fire risk.
- ▶ Heat may cause expansion or decomposition with violent rupture of containers.

# Fire/Explosion Hazard

Decomposes on heating and produces toxic fumes of:

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

Issue Date: **08/05/2015** Print Date: **08/12/2016** 

HAZCHEM

Not Applicable

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul> Moderate hazard.
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 HANDLING AND STORAGE**

#### Precautions for safe handling

Safe handling  No special handling procedures required. Use good occupational work practice.	
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Store out of direct sunlight</li> <li>Store below 30 deg. C.</li> </ul>

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>	
Storage incompatibility	► Avoid reaction with oxidising agents	

#### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Control parameters**

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	isopropanol	Isopropyl alcohol	983 mg/m3 / 400 ppm	1230 mg/m3 / 500 ppm	Not Available	Not Available
Australia Exposure Standards	ethanolamine	Ethanolamine	7.5 mg/m3 / 3 ppm	15 mg/m3 / 6 ppm	Not Available	Not Available
Australia Exposure Standards	dipropylene glycol monomethyl ether	(2-Methoxymethylethoxy) propanol	308 mg/m3 / 50 ppm	Not Available	Not Available	Sk

#### EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
isopropanol	Isopropyl alcohol	400 ppm	2000 ppm	12000 ppm
ethanolamine	Ethanolamine	6 ppm	170 ppm	1,000 ppm
dipropylene glycol monomethyl ether	Dipropylene glycol methyl ether	150 ppm	1700 ppm	9900 ppm

Issue Date: **08/05/2015** Print Date: **08/12/2016** 

#### Septone C-Thru

Ingredient	Original IDLH	Revised IDLH
isopropanol	12,000 ppm	2,000 [LEL] ppm
non hazardous ingredients	Not Available	Not Available
ethanolamine	1,000 ppm	30 ppm
dipropylene glycol monomethyl ether	Unknown mg/m3 / Unknown ppm	600 ppm
water	Not Available	Not Available

#### **Exposure controls**

Exposure controls	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.  The basic types of engineering controls are:  Process controls which involve changing the way a job activity or process is done to reduce the risk.  Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	No special equipment for minor exposure i.e. when handling small quantities.  OTHERWISE:  Safety glasses with side shields.  Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	No special equipment needed when handling small quantities.  OTHERWISE: Wear general protective gloves, e.g. light weight rubber gloves.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities.  OTHERWISE:  Overalls.  Barrier cream.  Eyewash unit.
Thermal hazards	Not Available

# **Respiratory protection**

Type AEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

#### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

# Information on basic physical and chemical properties Clear pale blue mobile liquid with an alcoholic od

Appearance	Clear pale blue mobile liquid with an alcoholic odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	0.98 @ 25C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	10.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available

Issue Date: **08/05/2015** Print Date: **08/12/2016** 

#### Septone C-Thru

Initial boiling point and boiling range (°C)	82-187	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	>1 water=1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	>99
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	94.95

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

# Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.  There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.  There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

	TOXICITY	IRRITATION
Septone C-Thru	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 12792 mg/kg <sup>[1]</sup>	Eye (rabbit): 10 mg - moderate
isopropanol	Inhalation (rat) LC50: 72.6 mg/L/4hr <sup>[2]</sup>	Eye (rabbit): 100 mg - SEVERE
	Oral (rat) LD50: 5000 mg/kg <sup>[2]</sup>	Eye (rabbit): 100mg/24hr-moderate
		Skin (rabbit): 500 mg - mild
	TOXICITY	IRRITATION
ethanolamine	Dermal (rabbit) LD50: 1020 mg/kg <sup>[2]</sup>	Eye (rabbit): 0.76 mg - SEVERE

	Oral (rat) LD50: 1091.4 mg/kg <sup>[1]</sup>	Skin (rabbit):	505 mg open-moderate
	TOXICITY	IRRITATION	
dipropylene glycol	dermal (rat) LD50: >19000 mg/kg <sup>[1]</sup>	Eye (human	): 8 mg - mild
	Oral (rat) LD50: 5130 mg/kg <sup>[1]</sup>	Eye (rabbit):	500 mg/24hr - mild
monomethyl ether		Skin (rabbit)	: 238 mg - mild
		1	500 mg (open)-mild
	TOXICITY	IRRITATION	
water	Oral (rat) LD50: >90000 mg/kg <sup>[2]</sup>	Not Availabl	е
Legend:	Value obtained from Europe ECHA Registered		
	Unless otherwise specified data extracted from I	RTECS - Register of Toxic Eff	ect of chemical Substances
ISOPROPANOL	the skin or when inhaled. The substance is classified by IARC as Group 3 NOT classifiable as to its carcinogenicity to hum	em and drowsiness. Few have 3: nans.	kin. Prolonged high dose exposure may also e reported skin irritation. It can be absorbed from
ETHANOLAMINE	Evidence of carcinogenicity may be inadequate or limited in animal testing.  While it is difficult to generalise about the full range of potential health effects posed by exposure to the many different amine compounds, characterised by those used in the manufacture of polyurethane and polyisocyanurate foams, it is agreed that overexposure to the majority of these materials may cause adverse health effects.  • Many amine-based compounds can induce histamine liberation, which, in turn, can trigger allergic and other physiological effects, including bronchoconstriction or bronchial asthma and rhinitis.  • Systemic symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, tachycardia (rapid heartbeat), itching, erythema (reddening of the skin), urticaria (hives), and facial edema (swelling). Systemic effects (those affecting the body) that are related to the pharmacological action of amines are usually transient.  The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
DIPROPYLENE GLYCOL MONOMETHYL ETHER	for propylene glycol ethers (PGEs):  Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM).  Testing of a wide variety of propylene glycol ethers Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on reproductive organs, the developing embryo and fetus, blood (haemolytic effects), or thymus, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces an alkoxyacetic acid.  The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
WATER	No significant acute toxicological data identified in literature search.		
ISOPROPANOL & ETHANOLAMINE & DIPROPYLENE GLYCOL MONOMETHYL ETHER	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
ETHANOLAMINE & DIPROPYLENE GLYCOL MONOMETHYL ETHER	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.		
Acute Toxicity	0	Carcinogenicity	0
Skin	0	Reproductivity	0
Irritation/Corrosion Serious Eye		STOT - Single	
Damage/Irritation	0	Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Issue Date: 08/05/2015 Print Date: 08/12/2016

Legena:

👅 – Data avaliable but does not till the criteria for classification

✓ – Data required to make classification available

#### **SECTION 12 ECOLOGICAL INFORMATION**

#### **Toxicity**

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
isopropanol	LC50	96	Fish	183.844mg/L	3
isopropanol	EC50	48	Crustacea	12500mg/L	5
isopropanol	EC50	96	Algae or other aquatic plants	993.232mg/L	3
isopropanol	EC50	384	Crustacea	42.389mg/L	3
isopropanol	NOEC	5760	Fish	0.02mg/L	4
ethanolamine	LC50	96	Fish	=75mg/L	1
ethanolamine	EC50	48	Crustacea	=65mg/L	1
ethanolamine	EC50	72	Algae or other aquatic plants	=15mg/L	1
ethanolamine	EC50	504	Crustacea	2.5mg/L	2
ethanolamine	NOEC	504	Crustacea	0.85mg/L	2
dipropylene glycol monomethyl ether	LC50	96	Fish	1307.253mg/L	3
dipropylene glycol monomethyl ether	EC50	48	Crustacea	1930mg/L	2
dipropylene glycol monomethyl ether	EC50	72	Algae or other aquatic plants	>969mg/L	2
dipropylene glycol monomethyl ether	EC50	384	Crustacea	297.071mg/L	3
dipropylene glycol monomethyl ether	NOEC	72	Algae or other aquatic plants	969mg/L	2
Legend:	3. EPIWIN Suite	V3.12 - Aquatic Toxicity Data	rope ECHA Registered Substances - a (Estimated) 4. US EPA, Ecotox dat apan) - Bioconcentration Data 7. MET	abase - Aquatic Toxicity	Data 5. ECETO

**DO NOT** discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
isopropanol	LOW (Half-life = 14 days)	LOW (Half-life = 3 days)
ethanolamine	LOW	LOW
dipropylene glycol monomethyl ether	HIGH	HIGH
water	LOW	LOW

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
isopropanol	LOW (LogKOW = 0.05)
ethanolamine	LOW (LogKOW = -1.31)
dipropylene glycol monomethyl ether	LOW (BCF = 100)
water	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
isopropanol	HIGH (KOC = 1.06)
ethanolamine	HIGH (KOC = 1)
dipropylene glycol monomethyl ether	LOW (KOC = 10)

Issue Date: 08/05/2015 Print Date: 08/12/2016

water

LOW (KOC = 14.3)

#### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- ▶ Reuse
- Recycling
- Disposal (if all else fails)

#### **Product / Packaging** disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- ► Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- ▶ Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material).
- ▶ Decontaminate empty containers.

#### **SECTION 14 TRANSPORT INFORMATION**

#### **Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### **SECTION 15 REGULATORY INFORMATION**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### ISOPROPANOL(67-63-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

#### ETHANOLAMINE(141-43-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER(34590-94-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

#### WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (ethanolamine; water; dipropylene glycol monomethyl ether; isopropanol)

Chemwatch: **7503-35** Page 10 of 10 Issue Date: 08/05/2015 Version No: 8.1.1.1 Print Date: 08/12/2016

#### Septone C-Thru

China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 OTHER INFORMATION**

#### Other information

# Ingredients with multiple cas numbers

Name	CAS No
dipropylene glycol monomethyl ether	34590-94-8, 12002-25-4, 112388-78-0, 104512-57-4, 83730-60-3, 112-28-7, 13429-07-7, 20324-32-7, 13588-28-8, 55956-21-3

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

#### www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.